

Mn-Zn-Ferrite Tile for Anechoic Chamber

未来を支える粒子になる。



Specification of Performance

6.7mm

Frequency	Typical	Specification
30 MHz	-25.0dB	-19.5dB Max
50 MHz	-29.0dB	
100 MHz	-31.0dB	
300 MHz	-20.0dB	
500 MHz	-15.0dB	
700 MHz	-12.0dB	
1000 MHz	-10.5dB	-10.0dB Max


5.2mm

Frequency	Typical	Specification
30 MHz	-22.0dB	-19.5dB Max
50 MHz	-27.0dB	
100 MHz	-39.0dB	
300 MHz	-23.0dB	
500 MHz	-17.0dB	
700 MHz	-15.0dB	
1000 MHz	-12.0dB	-10.0dB Max

Part number and Dimension

6.7mm

PART No.	Dimension(mm)		Weight
TILE 67	A : Width	100 ± 0.1	$\approx 331g$
	B : Length	100 ± 0.1	
	C : Thickness	6.7 ± 0.1	
	D : Hole	10 ± 0.2	
	E : Squareness	< 0.15	



5.2mm

PART No.	Dimension(mm)		Weight
TILE 52	A : Width	100 ± 0.1	$\approx 253g$
	B : Length	100 ± 0.1	
	C : Thickness	5.2 ± 0.1	
	D : Hole	10 ± 0.2	
	E : Squareness	< 0.15	

